




## ELECTROSTATIC PRECIPITATOR: CV-ESP-3D

Model	CV-ESP-3D
Air Flow (L/s)	900-3000
Recommended Air Velocity (m/s)	1-2 (Heavy Cooking)
Recommended Air Velocity (m/s)	2-3 (Moderate Cooking)
Recommended Air Velocity (m/s)	3-4 (Light Cooking)
Cabinet Material	Carbon Steel (1.2mm)
Finishing	Powder-Coated (Off White)
Cabinet Size L*W*H (mm)	1110*1835*690
Flange Size A*B (mm)	1560*530
Removal Efficiency Rate	Up to 99% (Tested by ASHRAE 52.2-2017)
Static Pressure (Pa)	80 (Clean) - 180 (Dirty)
Pre Filter	3
Power Consumption (Watt)	660
Power Pack	High-Hz High-V Solid-State Transformer
Power Supply	240V / 1 PH / 50~60 Hz / 3A
Air Flow Direction	Left-Right / Right-Left (Reversible)
Cell Qty (PCS)	6
Each Cell Size L*W*H (mm)	535*320*515
Collection Area (m <sup>2</sup> /unit)	27.93
Indicators	LED Lights For Power & Faults
Insulator Material	Ceramic
Net Weight (kg)	254
Service Area (mm)	1200*650



CONTROL BOX  
CV-ESP-CTB



CELL  
CV-ESP-CEL




PRE FILTER  
CV-ESP-FLT



GREASE TRAY  
CV-ESP-GTY

### REPLACEMENT PARTS AVAILABLE



29 Liverpool St  
Ingleburn NSW 2565  
Ph: 1300 422 825

info@cavaliervent.com.au  
www.cavaliervent.com.au